

# CHANGE C-SHAPE CHAIR MODEL 7813



## STANDARD VERSION

PAGHOLZ® waisted shell, with ergonomic three-dimensional shell shape and handle slot. Surface melamine coated and pore sealed with a scratch, impact and abrasion resistant finish created in the pressing process. Edges and waist are milled.

C-shape frame, round tube: 22/2.5 mm, standard version epoxy coated. With 3-component floor protector A2S FLOORSAFE®. Including plate and edge protectors to rest on the table top.

## OPTIONS

- Seat upholstery price group 1
- Backrest upholstery price group 1
- Seat upholstery price group 2
- Backrest upholstery price group 2
- Seat upholstery price group 3
- Backrest upholstery price group 3
- Seat upholstery price group 4
- Backrest upholstery price group 4
- FLOORSAFE® felt floor protectors
- Chair frame chrome plated
- Cross brace (size 5-7)
- Row connection (size 5-7)

## STANDARD

FEMB level:2017 (Level 3)

DIN EN 1729-1, DIN EN 1729-2

## LOAD CAPACITY

125 kg

## SIZES

SIZE	6
CHAIR WIDTH	52 cm
CHAIR HEIGHT	78 cm
SEAT HEIGHT	46 cm
CHAIR DEPTH	49 cm
STACKABILITY	5 pcs.
WEIGHT	4 kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.  
ASS-Einrichtungssysteme GmbH  
info@a2s.com  
WWW.A2S.COM

# CHANGE C-SHAPE CHAIR MODEL 7813



## BENEFITS/SPECIALS



PAGHOLZ® from sustainable forestry



Optionally with seat and backrest upholstery



Plate and edge protectors protect the table when it is upended




Optionally with row connection from size 5



Indestructible PAGHOLZ® shell, scratch, break and impact resistant; flame retardant



Robust C-shape frame with A2S FLOORSAFE® floor protectors



Stackable up to 5 chairs (without upholstery)



Easy to carry due to light weight

## FABRIC PROPERTIES

### INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m<sup>2</sup> +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

### SKANDIA Price group 1

100% polyester | flame retardant according to EN 1021 1 | 245 g/m<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

### FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m<sup>2</sup> | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

### TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

### WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m<sup>2</sup> +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

### PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m<sup>2</sup> | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

### ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m<sup>2</sup> +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

### ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m<sup>2</sup> | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants