

WOODMARK GAS LIFT SWIVEL CHAIR WITH FOOT RING

MODEL 8382.002



STANDARD VERSION

Seat and back separate and shaped to fit the body. Made of multiplex, surface melamine coated and pore sealed with a scratch, impact and abrasion resistant finish produced in the pressing process.

In beech D334 as standard. Seat surface with pressed-in, anti-slip knobs. Edges softly rounded.

Aluminum 5-star base, with infinitely variable gas lift height adjustment. Round tubular column: 50 mm, epoxy coated. Version with elevation and height-adjustable foot ring, chrome-plated. With plastic feet.

Distance seat floor 495 - 709 mm

OPTIONS

- WOODMARK maple D033 or gray white U023
- Seat and back riveted
- Load-dependent braking casters (SH +3 cm)
- Seat and back color stained
- Felt floor protectors
- Polished aluminum base

STANDARD

FEMB level:2017 (Level 3)

DIN EN 1729-1, DIN EN 1729-2, DIN EN 16139

GS-zertifiziert gem. DIN EN 1729-1, DIN EN 1729-2

LOAD CAPACITY

125 kg

SIZES

SIZE	5-7
CHAIR WIDTH	66 cm
CHAIR HEIGHT	81-101 cm
SEAT HEIGHT	50-70 cm
CHAIR DEPTH	66 cm
STACKABILITY	-
WEIGHT	9 kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM

WOODMARK GAS LIFT SWIVEL CHAIR WITH FOOT RING

MODEL 8382.002



BENEFITS/SPECIALS



Robust aluminum base with elevation and chrome-plated foot ring, height adjustable



Height adjustment by safety gas spring



Seat surface with pressed-in, anti-slip knobs



Seat and back concealed screwed



Seat and back melamine coated: scratch, break and impact resistant; flame retardant