PREMIUM OFFICE SWIVEL CHAIR WITH MESH BACKREST AND HEADREST

MODEL 9349.001





STANDARD VERSION

Fully upholstered seat and black mesh back. Synchronous dynamic movement with locking of the back in 5 positions. Seat inclination and seat depth adjustable: back 20°, seat 6° as well as seat depth adjustment range 6 cm. Backrest 56 cm high, with independent lumbar support adjustment. 5-star aluminum base, with infinitely variable gas lift height adjustment including seat depth suspension: 45 - 56 cm. Polished aluminum base, with load-dependent braked safety casters.

Including headrest, 15 cm high, black mesh. Tiltable and height adjustable by 7.5 cm.

OPTIONS

- Upholstery fabric price group 2
- Upholstery fabric price group 3
- Upholstery fabric price group 4
- Soft casters for hard floors

STANDARD

DIN EN 1729-1, DIN EN 1729-2

LOAD CAPACITY

110 kg

SIZES

| CHAIR WIDTH | 69 cm |
|--------------|------------|
| CHAIR HEIGHT | 122-139 cm |
| SEAT HEIGHT | 45-56 cm |
| CHAIR DEPTH | 69 cm |
| STACKABILITY | - |
| WEIGHT | 16 kg |
| | |

Our range of materials and colors can be found in the A2S material overview.





PREMIUM OFFICE SWIVEL CHAIR WITH MESH BACKREST AND HEADREST

MODEL 9349.001



BENEFITS/SPECIALS



Elegant, high-quality aluminum base



Load-dependent braked safety casters prevent unintentional rolling away



Black mesh backrest, with lumbar support adjustment



Ergonomically shaped, breathable mesh backrest



Headrest with mesh cover, height adjustable



Stepless gas lift height adjustment includes seat depth suspension



Self-weighing synchronous mechanism automatically adjusts spring force or resistance

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m2 +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100 SKANDIA Price group 1

100% polyester | flame retardant according to EN 10211 | 245 g/m2 +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100 FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m2 | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100 TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m2 +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100 WOOL Price group 3

100% wool | flame retardant according to EN 10211&2 | 460 g/m2 +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m2 | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m2 +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 10211&2, DIN 4102 B1 | weight 780+/-50 g/m2 | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants