

# STANDARD OFFICE SWIVEL CHAIR WITH FULL UPHOLSTERY AND ARMRESTS

MODEL 9352.102



## STANDARD VERSION

Fully upholstered seat and back. Synchronous mechanism with locking of the back in 4 positions. Seat inclination adjustable: back 22°, seat 13°.

Backrest 56 cm high, height adjustable by 8 cm, with lumbar support adjustment in the range 15 mm.

5-star black plastic base with infinitely variable gas lift height adjustment, including seat depth suspension: 45 - 56 cm. With load-dependent braked safety casters.

Including armrests in soft plastic, height adjustable by 8 cm.

## OPTIONS

- Upholstery fabric price group 2
- Upholstery fabric price group 3
- Upholstery fabric price group 4
- Soft casters for hard floors

## STANDARD

DIN EN 1729-1, DIN EN 1729-2

## LOAD CAPACITY

110 kg

## SIZES

|              |            |
|--------------|------------|
| CHAIR WIDTH  | 70 cm      |
| CHAIR HEIGHT | 100-116 cm |
| SEAT HEIGHT  | 45-56 cm   |
| CHAIR DEPTH  | 70 cm      |
| STACKABILITY | -          |
| WEIGHT       | 15 kg      |

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.  
ASS-Einrichtungssysteme GmbH  
info@a2s.com  
WWW.A2S.COM

# STANDARD OFFICE SWIVEL CHAIR WITH FULL UPHOLSTERY AND ARMRESTS

MODEL 9352.102



## BENEFITS/SPECIALS



Elegant, sturdy black plastic base




Load-dependent braked safety casters prevent unintentional rolling away



Ergonomically shaped backrest



Height adjustable armrests



Stepless gas lift height adjustment includes seat depth suspension



Synchronous mechanism: Spring force or resistance adjustable to body weight

## FABRIC PROPERTIES

### INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m<sup>2</sup> +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

### SKANDIA Price group 1

100% polyester | flame retardant according to EN 1021 1 | 245 g/m<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

### FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m<sup>2</sup> | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

### TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

### WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m<sup>2</sup> +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

### PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m<sup>2</sup> | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

### ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m<sup>2</sup> +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

### ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780 +/-50 g/m<sup>2</sup> | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants