

# CANTILEVER CONFERENCE CHAIR FULLY UPHOLSTERED

## MODEL 9253.001



### STANDARD VERSION

Fully upholstered seat and back. Backrest 39 cm.

Cantilever frame, round tube. Standard version chrome-plated, with plastic floor protectors.

### OPTIONS

- Upholstery fabric price group 2
- Upholstery fabric price group 3
- Upholstery fabric price group 4
- Felt floor protectors

### LOAD CAPACITY

110 kg

### SIZES

CHAIR WIDTH	53 cm
CHAIR HEIGHT	83 cm
SEAT HEIGHT	46 cm
CHAIR DEPTH	57 cm
STACKABILITY	-
WEIGHT	8 kg


### BENEFITS/SPECIALS



Ergonomically shaped backrest



Robust cantilever frame



Stackable up to 4 chairs

Our range of materials and colors can be found in the A2S material overview.



# CANTILEVER CONFERENCE CHAIR FULLY UPHOLSTERED

## MODEL 9253.001



### FABRIC PROPERTIES

#### **INTENSIVE Price group 1**

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m<sup>2</sup> +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

#### **SKANDIA Price group 1**

100% polyester | flame retardant according to EN 1021 1 | 245 g/m<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

#### **FLEECE Price group 1**

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m<sup>2</sup> | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

#### **TAFF B1 Price group 2**

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

#### **WOOL Price group 3**

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m<sup>2</sup> +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

#### **PROTEX Price group 3**

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m<sup>2</sup> | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

#### **ARTIFICIAL LEATHER Price group 3**

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m<sup>2</sup> +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

#### **ARTIFICIAL LEATHER B1 Price group 4**

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m<sup>2</sup> | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants