

# UPHOLSTERED SWIVEL CHAIR MODEL 9370



## STANDARD VERSION

Fully upholstered seat, foam padding. 3-color version possible, colors can be selected separately within a fabric group: seat (inside), seat bottom (outside) and backrest (outside). Backrest 47 cm.

Aluminum base, 5-star with infinitely variable gas lift height adjustment, includes rocker mechanism with locking. Polished aluminum base, with load-dependent braked safety casters.

## OPTIONS

- Upholstery fabric price group 2
- Upholstery fabric price group 3
- Upholstery fabric price group 4
- Soft casters for hard floors

## STANDARD

GS-zertifiziert gem. DIN EN 16139

## LOAD CAPACITY

110 kg

## SIZES

|              |          |
|--------------|----------|
| CHAIR WIDTH  | 70 cm    |
| CHAIR HEIGHT | 82-91 cm |
| SEAT HEIGHT  | 44-53 cm |
| CHAIR DEPTH  | 70 cm    |
| STACKABILITY | -        |
| WEIGHT       | 13 kg    |

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.  
ASS-Einrichtungssysteme GmbH  
info@a2s.com  
WWW.A2S.COM

# UPHOLSTERED SWIVEL CHAIR MODEL 9370




## BENEFITS/SPECIALS



Durable due to high quality workmanship



Ergonomically shaped fully upholstered seat with form-integrated armrests



Optionally upholstered in 3-color design



Height adjustment by safety gas spring



Elegant, high-quality aluminum base



Load-dependent braked safety casters prevent unintentional movement

## FABRIC PROPERTIES

### **INTENSIVE Price group 1**

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m<sup>2</sup> +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

### **SKANDIA Price group 1**

100% polyester | flame retardant according to EN 1021 1 | 245 g/m<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

### **FLEECE Price group 1**

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m<sup>2</sup> | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

### **TAFF B1 Price group 2**

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

### **WOOL Price group 3**

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m<sup>2</sup> +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

### **PROTEX Price group 3**

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m<sup>2</sup> | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

### **ARTIFICIAL LEATHER Price group 3**

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m<sup>2</sup> +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

### **ARTIFICIAL LEATHER B1 Price group 4**

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780 +/-50 g/m<sup>2</sup> | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants