

FLEX Z-SHAPE CHAIR MODEL 7853



STANDARD VERSION

Plastic shell ergonomically shaped. Material made of polypropylene, recyclable, manufactured in double-wall blown process. Thus soft sitting due to air cushioning effect, with integrated ventilation channels and groove to relieve the spine. Grip hole in the lumbar region and recessed grips on the upper edge of the backrest and underside of the chair.

Z-shaped frame with 3D rocking effect, sizes 2-4 round tube: 22/2.5 mm, sizes 5-7 round tube: 22/3.0 mm, epoxy coated. With 3-component floor protector A2S FLOORSAFE®. To be placed on the table top.

OPTIONS

- FLOORSAFE® felt floor protectors
- Chair frame chrome plated
- Fully upholstered FLEX (size 5-7)

STANDARD

FEMB level:2017 (Level 3)

DIN EN 1729-1, DIN EN 1729-2, DIN EN 16139

LOAD CAPACITY

125 kg

SIZES

| SIZE | 2 | 3 | 4 | 5 | 6 | 7 |
|--------------|--------|--------|--------|--------|--------|--------|
| CHAIR WIDTH | 39 cm | 39 cm | 39 cm | 45 cm | 45 cm | 45 cm |
| CHAIR HEIGHT | 62 cm | 66 cm | 69 cm | 79 cm | 82 cm | 87 cm |
| SEAT HEIGHT | 31 cm | 35 cm | 38 cm | 43 cm | 46 cm | 51 cm |
| CHAIR DEPTH | 37 cm | 39 cm | 39 cm | 53 cm | 53 cm | 53 cm |
| STACKABILITY | 2 pcs. | 2 pcs. | 2 pcs. | 2 pcs. | 2 pcs. | 2 pcs. |
| WEIGHT | 4 kg | 4 kg | 5 kg | 6 kg | 6 kg | 6 kg |

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM

FLEX Z-SHAPE CHAIR MODEL 7853



BENEFITS/SPECIALS



Easy to carry due to low weight



3D movement through Z-frame supports the toning of the muscles



Optional seat shell fully upholstered from size 5 onwards



Seat shell with integrated ventilation channel



Robust Z-shape frame with A2S FLOORSAFE® floor protectors



Plate protectors protect the table when stacking up



2 chairs stackable and easy to carry due to low weight



Shell shape allows different sitting positions, including reverse

FABRIC PROPERTIES

FLEX upholstery

Flame retardant according to DIN 4102 B1 | 250 g/m² +/-5% | 40,000 Martindale tours | Linting 4 | ÖKO-Tex 100