

FLEX FOOTREST CHAIR MODEL 7416.046



STANDARD VERSION

Plastic shell ergonomically shaped. Material made of polypropylene, recyclable, manufactured in double-wall blown process. Thus soft sitting due to air cushioning effect, with integrated ventilation channels and groove to relieve the spine. Grip hole in the lumbar region and recessed grips on the upper edge of the backrest and underside of the chair.

Cantilever frame, round tube: 22/2.5 mm, epoxy coated. Footrest solid core 12 mm, easy adjustment by one-hand operation. With plastic floor protector.

For table height ISO 6 / 76 cm.

OPTIONS

- Felt floor protectors
- Chair frame chrome plated

STANDARD

FEMB level:2017 (Level 3)

GS-zertifiziert gem. DIN EN 1729-1, DIN EN 1729-2

DIN EN 16139

LOAD CAPACITY

125 kg

SIZES

| | |
|--------------|------------|
| SIZE | 3-4, 40 cm |
| CHAIR WIDTH | 49 cm |
| CHAIR HEIGHT | 87 cm |
| SEAT HEIGHT | 36-40 cm |
| CHAIR DEPTH | 54 cm |
| STACKABILITY | 3 pcs. |
| WEIGHT | 7 kg |

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM

FLEX FOOTREST CHAIR MODEL 7416.046



BENEFITS/SPECIALS



Easy to carry due to low weight



Tilt protection due to special floor protectors



Tool-free adjustment of the footrest with only one hand



Seat shell with integrated ventilation channel



Stackable up to 3 chairs