FLEX FOOTREST CHAIR MODEL 7416.046





STANDARD VERSION

Plastic shell ergonomically shaped. Material made of polypropylene, recyclable, manufactured in double-wall blown process. Thus soft sitting due to air cushioning effect, with integrated ventilation channels and groove to relieve the spine. Grip hole in the lumbar region and recessed grips on the upper edge of the backrest and underside of the chair.

LOAD CAPACITY

125 kg

Cantilever frame, round tube: 22/2.5 mm, epoxy coated. Footrest solid core 12 mm, easy adjustment by one-hand operation. With plastic floor protector.

For table height ISO $6 / 76 \ \text{cm}$.

OPTIONS

Felt floor protectors

Chair frame chrome plated

STANDARD

FEMB level:2017 (Level 3)

GS-zertifiziert gem. DIN EN 1729-1, DIN EN 1729-2

DIN EN 16139

SIZES

SIZE	3-4, 40 cm
CHAIR WIDTH	49 cm
CHAIR HEIGHT	87 cm
SEAT HEIGHT	36-40 cm
CHAIR DEPTH	54 cm
STACKABILITY	3 pcs.
WEIGHT	7 kg

Our range of materials and colors can be found in the A2S material overview.









FLEX FOOTREST CHAIR MODEL 7416.046



BENEFITS/SPECIALS







Tilt protection due to special floor protectors



Tool-free adjustment of the footrest with only one hand



Seat shell with integrated ventilation channel



Stackable up to 3 chairs