

WOODMARK C-FRAME CHAIR WITH SEAT AND BACKREST UPHOLSTERY

MODEL 7106



STANDARD VERSION

Seat and back separate and shaped to fit the body. Seat support made of beech plywood, fully upholstered all round.

C-shape frame, side part oval tube: 35/15/2 mm, seat support rectangular tube: 30/15/2 mm, cross strut oval tube: 35/15/1.5 mm, standard version epoxy coated. Including plate protector to sit on the table top. Floor protector with step protection.

OPTIONS

- Upholstery fabric price group 2
- Upholstery fabric price group 3
- Upholstery fabric price group 4
- Seat and back riveted
- Felt floor protectors
- Row connection

STANDARD

FEMB level:2017 (Level 3)

DIN EN 1729-1, DIN EN 1729-2

LOAD CAPACITY

125 kg

SIZES

SIZE	6	7
CHAIR WIDTH	45 cm	45 cm
CHAIR HEIGHT	79 cm	83 cm
SEAT HEIGHT	48 cm	52 cm
CHAIR DEPTH	51 cm	51 cm
STACKABILITY	-	-
WEIGHT	7 kg	8 kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM

WOODMARK C-FRAME CHAIR WITH SEAT AND BACKREST UPHOLSTERY

MODEL 7106



BENEFITS/SPECIALS




Floor protectors with integrated step protection



Plate protectors protect the table when stacking



With seat and backrest upholstery



Optionally with row connection



Stable and solid C-shape frame



No disturbance of the chair legs when getting in and out of the chair

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

SKANDIA Price group 1

100% polyester | flame retardant according to EN 10211 | 245 g/m² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m² | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m² +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m² | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants