

# CANTILEVER CHAIR WITH FULL UPHOLSTERY MODEL 7419.011



## STANDARD VERSION

Straight, rectangular seat shell, shaped to fit the body, with concealed fastening. Seat support made of beech plywood, fully upholstered. Cantilever frame, firmly welded. Round tube: 22/2.5 mm. Frame chrome-plated, with plastic floor protectors.

## OPTIONS

- Full upholstery price group 2
- Full upholstery price group 3 (imitation leather)
- Full upholstery price group 3 (PROTEX)
- Full upholstery price group 3 (WOOL)
- Full upholstery price group 4 (artificial leather B1)
- Felt floor protectors

## LOAD CAPACITY

125 kg

## SIZES

SIZE	6
CHAIR WIDTH	44 cm
CHAIR HEIGHT	89 cm
SEAT HEIGHT	46 cm
CHAIR DEPTH	55 cm
STACKABILITY	-
WEIGHT	8 kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.  
ASS-Einrichtungssysteme GmbH  
info@a2s.com  
WWW.A2S.COM

# CANTILEVER CHAIR WITH FULL UPHOLSTERY MODEL 7419.011



## BENEFITS/SPECIALS



Body contoured seat shell with full upholstery



Extremely robust cantilever frame

## FABRIC PROPERTIES

### **INTENSIVE Price group 1**

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m<sup>2</sup> +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

### **SKANDIA Price group 1**

100% polyester | flame retardant according to EN 1021 1 | 245 g/m<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

### **FLEECE Price group 1**

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m<sup>2</sup> | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

### **TAFF B1 Price group 2**

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

### **WOOL Price group 3**

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m<sup>2</sup> +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

### **PROTEX Price group 3**

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m<sup>2</sup> | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

### **ARTIFICIAL LEATHER Price group 3**

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m<sup>2</sup> +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

### **ARTIFICIAL LEATHER B1 Price group 4**

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m<sup>2</sup> | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants