

#### STANDARD VERSION

Straight, rectangular seat shell, shaped to fit the body, with concealed fastening. Seat support made of beech plywood, fully upholstered.

Cantilever frame incl. armrest with black softgrip cover, firmly welded. Round tube 22/2.5 mm. Frame chrome-plated, with plastic floor protectors.

## **OPTIONS**

- Full upholstery price group 2
- Full upholstery price group 3 (imitation leather)
- Full upholstery price group (PROTEX)
- Full upholstery price group 3 (WOOL)
- Full upholstery price group 4 (artificial leather B1)
- Felt floor protectors

## LOAD CAPACITY

125 kg

## SIZES

SIZE	6
CHAIR WIDTH	54 cm
CHAIR HEIGHT	91 cm
SEAT HEIGHT	45 cm
CHAIR DEPTH	52 cm
STACKABILITY	-
WEIGHT	8 kg

# BENEFITS/SPECIALS







Body contoured seat shell with full upholstery



Robust cantilever frame with armrest

# FABRIC PROPERTIES

# INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m2 +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

### **SKANDIA Price group 1**

100% polyester | flame retardant according to EN 1021 1 | 245 g/m2 +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex

## FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m2 | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

### TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m2 +/-5% | 70,000 Martindale tours | linting 5 I ÖKO-Tex 100

WOOL Price group 3
100% wool | flame retardant according to EN 1021 1&2 | 460 g/m2 +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

#### **PROTEX Price group 3**

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m2 | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

#### **ARTIFICIAL LEATHER Price group 3**

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m2 +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m2 | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants