

# OFFICE DESK, ELECTRICALLY HEIGHT ADJUSTABLE (200X160 CM)

MODEL 5586.208



## STANDARD VERSION

Tabletop, 3-layer chipboard (E1), melamine coated, highly abrasion-resistant, with 3 mm plastic edge, thickness: 25 mm.

**Note:** Table height specifications refer to a tabletop thickness of 25 mm.

Maximum load capacity of table top: 100 kg.

Center column frame height adjustable by electric motor, rectangular steel tube. Lifting speed: 38 mm/s (without load). Lifting load per column: 800 N. Foldable metal cable tray under the table top including 6-fold Schuko socket with 3 m cable supply. Powder coated frame. Steel runners with plastic floor protectors with level compensation.

Table top shape: L-shaped

## OPTIONS

- Table top finishes price group 2
- Table top HPL glued
- Cable opening, Ø 80 mm
- Cable opening, Ø 90 mm
- CPU holder
- Cable slack
- Table frame black
- Table frame white
- Manual switch with memory function

## STANDARD

GS-zertifiziert gem. EK5/AK3 13-01

## SIZES

TABLE HEIGHT	62-127 cm
TABLE DEPTH	80 cm
PLAN DIMENSION	200x160 cm
STACKABILITY	-
NUMBER OF SEATS	1
WEIGHT	86 kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.  
ASS-Einrichtungssysteme GmbH  
info@a2s.com  
WWW.A2S.COM

# OFFICE DESK, ELECTRICALLY HEIGHT ADJUSTABLE (200X160 CM)

MODEL 5586.208



## BENEFITS/SPECIALS



Melamine coated table top with robust plastic edge



Manual switch with up and down function or optional memory function



Concealed cable management through foldable cable tray



Floor protectors with level compensation for easy leveling of uneven floors



Collision protection minimizes the risk of damage when moving up and down



Matching accessories: front panel model 2050.202



Infinitely and quietly height adjustable in the range 62-127 cm