



STANDARD VERSION

Unterkonstruktion aus stabiler 3-Schicht-Spanplatte mit Polsterung aus Schaumstoff. Rundfüße pulverbeschichtet in RAL 7021 schwarzgrau aus Stahl. Farben der Lehne und Sitzfläche getrennt innerhalb einer Stoffgruppe wählbar.

Alle Elemente der Serie sind miteinander verkettbar.

Sitzhöhe: 38 cm

OPTIONS

- Upholstery fabric TAFF B1 (price group 2)
- Upholstery fabric PROTEX (price group 3)
- Upholstery fabric WOOL (price group 3)
- Bezugsstoff PROTEX B1

TECHNICAL SPECIFICATIONS

TOTAL WIDTH	95 cm
TOTAL HEIGHT	63 cm
SEAT HEIGHT	38 cm
TOTAL DEPTH	60 cm
SEAT DEPTH	43 cm
WEIGHT	18 kg

FABRIC PROPERTIES

FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m² | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

PROTEX B1 price group 4

surface 100% vinyl / fabric 100% cotton | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 760 g/m² | 300.000 tours Martindale | no linting

SPECIAL PROPERTIES: PERMABLOK3® - protection against germs, abrasion and stains: Antibacterial, antifungal, stain resistant, sulfide stain resistant, anti-fungal protection - mildew resistant backing and surface | disinfectant resistant, easy cleaning - wipeable with soap and water | antistatic surface

Tested to: ISO206B02 7/8 UV resistance | ISO 18184 & ISO 21702 virus-free surface to reduce corona virus | ISO 22196 for bacteria-free surface | ISO 16000 indoor air emission class A+

Tested for: Plasticizers and harmful substances - material requirements of toy standards EN 71-3 Safety of toys (migration of certain elements) and 2005/84/EC (phthalates in toys and childcare articles)