

## STANDARD VERSION

Tabletop, 3-layer chipboard (E1), melamine coated, highly abrasion-resistant, with 3 mm plastic edge, thickness: 25 mm. Note: Table height specifications refer to a tabletop thickness of 25 mm.

Center column frame height adjustable, side panels oval tube: 50/30/2 mm. Plate support steel angle: 30/30/3 mm. Crosspiece oval tube: 50/20/2 mm, welded in as cover. Height adjustment by locking in color-coded steps. Frame epoxy coated. Steel runners with plastic floor protectors with continuous step protection. With plate support in the middle and satchel hooks on both sides.

**Note:** It is not possible to combine the book storage basket and chair suspension equipment options.

## **OPTIONS**

- Felt floor protectorsTabletop with ASSODUR® edge
- Table top WOODMARK, 21.5 mm
- Table top glued with solid wood edge glue-in crowned
- Table top HPL gluedTable top compact board 12 mm
- Table top Multiplex, 20 mm
- Glossy, galvanized book basket
- Chair suspension C-shape chairs
- Chair suspension
- Chair suspension PAGHOLZ® sledbase chair

## **STANDARD**

DIN EN 1729-1, DIN EN 1729-2

FEMB level:2017 (Level 3)

## **BENEFITS/SPECIALS**





with robust plastic edge



Optional WOODMARK table top in shatterproof quality



Optional melamine coated table top with ASSODUR® edge



Includes one satchel hook per seat



Optional compact board as



Floor protector with continuous step protection



Optional table top multiplex



Optional melamine coated table top with solid wood edge