



STANDARD VERSION

Tabletop, 3-layer chipboard (E1), melamine coated, highly abrasion-resistant, with 3 mm plastic edge, thickness: 25 mm.

Note: Table height specifications refer to a tabletop thickness of 25 mm.

Center column frame height adjustable, side panels oval tube: 50/30/2 mm. Plate support steel angle: 30/30/3 mm. Crosspiece oval tube: 50/20/2 mm, welded in as cover. Height adjustment by locking in color-coded steps. Frame epoxy coated. Steel runners with plastic floor protectors with continuous step protection.

With plate support in the middle and satchel hooks on both sides.

Note: It is not possible to combine the book storage basket and chair suspension equipment options.

OPTIONS

- Felt floor protectors
- Tabletop with ASSODUR® edge
- Table top WOODMARK, 21.5 mm
- Table top glued with solid wood edge glue-in crowned
- Table top HPL glued
- Table top compact board 12 mm
- Table top Multiplex, 20 mm
- Glossy, galvanized book basket
- Chair suspension C-shape chairs
- Chair suspension
- Chair suspension PAGHOLZ® sled-base chair

STANDARD


DIN EN 1729-1, DIN EN 1729-2

FEMB level:2017 (Level 3)


BENEFITS/SPECIALS




Melamine coated table top with robust plastic edge



Optional melamine coated table top with ASSODUR® edge



Optional compact board as table top



Optional table top multiplex melamine coated



Optional melamine coated table top with solid wood edge



Optional WOODMARK table top in shatterproof quality



Includes one satchel hook per seat



Floor protector with continuous step protection