

STANDARD VERSION

Top, 3-layer chipboard (E1), melamine coated, highly abrasion resistant, with 3 mm plastic edge, thickness: 25 mm.

OPTIONS

- Decoration group 2
- magnetic
- Upholstery fabric Intensive
- Cover fabric Skandia
- Cover fabric fleece
- Upholstery fabric TAFF B1 (price group 2)
- Upholstery fabric WOOL (price group 3)
- Frame chrome plated

TECHNICAL SPECIFICATIONS


 WIDTH
 22.36 "

 HEIGHT
 18.11 "

 WEIGHT
 35 lb

BENEFITS/SPECIALS







Optionally with fabric cover



Ideal as a view and sound insulation

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 8.82 oz/y 2 +/-5% | 100,000 Martindale tours | linting 5 | \ddot{O} KO-Tex 100

SKANDIA Price group 1

100% polyester | flame retardant according to EN 1021 1 | 8.64 oz/ y^2 +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 14.18 oz/y² | 100,000 Martindale tours | linting 4 | ÖKO-Tex

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 9.17 oz/y 2 +/-5% | 70,000 Martindale tours | linting 5 | \ddot{O} KO-Tex 100

WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 16.23 oz/y² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances