# DOMINO STOOL
# MODEL 9384.001

## STANDARD VERSION

Upholstery over foam. Substructure made of robust 3-layer chipboard. Sturdy skid frame with plastic floor protector, powder-coated in RAL 9006 as standard. Can be linked with other DOMINO elements.

## OPTIONS

- Frame chrome plated
- Bezugsstoff TAFF B1 (P-a zertifiziert)
- Upholstery fabric price group 3
- Bezugsstoff KUNSTLEDER B1 (P-a zertifiziert)
- Bezugsstoff PROTEX B1 (P-a zertifiziert)
- Felt floor protectors
- Linking
- 9384.904 Set Bodenbefestigung, geklebt oder geschraubt

## STANDARD

FEMB level:2017 (Level 3)

DIN EN 16139, DIN EN 15372

bei Bezugsstoffen B1:
höchste zertifizierte Brandschutzsicherheit nach DIN 66084 P-a (Papierkissentest)

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| TOTAL WIDTH | 69 cm |
| SEAT WIDTH | 69 cm |
| TOTAL HEIGHT | 45 cm |
| SEAT HEIGHT | 45 cm |
| TOTAL DEPTH | 69 cm |
| SEAT DEPTH | 69 cm |
| WEIGHT | 18 kg |

Our range of materials and colors can be found in the A2S material overview.

MADE IN GERMANY

A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM

# DOMINO STOOL
# MODEL 9384.001

## BENEFITS/SPECIALS



Stable sled frame optionally chrome-plated

Durable due to high quality workmanship




Positioning the corner/outside elements

Optional mit geschraubter oder geklebter Bodenbefestigung

Optionally fire protection certified according to DIN 66084 P-a with cover fabric B1

Individually extendable through interlinkable elements

## FABRIC PROPERTIES

**INTENSIVE Price group 1**
100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m2 +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100
**SKANDIA Price group 1**
100% polyester | flame retardant according to EN 1021 1 | 245 g/m2 +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100
**FLEECE Price group 1**
100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m2 | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100
**TAFF B1 Price group 2**
100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m2 +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100
**WOOL Price group 3**
100% wool | flame retardant according to EN 1021 1&2 | 460 g/m2 +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances
**PROTEX Price group 3**
surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m2 | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants
**ARTIFICIAL LEATHER Price group 3**
surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m2 +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances
**ARTIFICIAL LEATHER B1 Price group 4**
85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m2 | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants
**PROTEX B1 price group 4**
surface 100% vinyl / fabric 100% cotton | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 760 g/m2 | 300.000 tours Martindale | no linting

**SPECIAL PROPERTIES:** PERMABLOK3® - protection against germs, abrasion and stains: Antibacterial, antifungal, stain resistant, sulfide stain resistant, anti-fungal protection - mildew resistant backing and surface | disinfectant resistant, easy cleaning - wipeable with soap and water | antistatic surface

**Tested to:** ISO206B02 7/8 UV resistance | ISO 18184 & ISO 21702 virus-free surface to reduce corona virus | ISO 22196 for bacteria-free surface | ISO 16000 indoor air emission class A+

**Tested for:** Plasticizers and harmful substances - material requirements of toy standards EN 71-3 Safety of toys (migration of certain elements) and 2005/84/EC (phthalates in toys and childcare articles)

A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM