# BAR STOOL
# MODEL 7899

## STANDARD VERSION

PAGHOLZ® waisted shell, with ergonomic three-dimensional shell shape. Surface melamine coated and pore sealed with a scratch, impact and abrasion resistant finish created in the pressing process. Seat and back surface with pressed-in texture.
Sled base with strong seat support plate, round tube: 25/2 mm, standard version epoxy coated. With footrest in natural lacquered solid beech. With plastic floor protector.

## OPTIONS

- PAGHOLZ® Color Wood - Price group 2
- PAGHOLZ® COLOUR WOOD
- Handle hole
- Seat upholstery price group 1 (size 6E, 7)
- Backrest upholstery price group 1 (size 6E, 7)
- Seat upholstery price group 2 (size 6E, 7)
- Back upholstery price group 2 (size 6E, 7)
- Seat upholstery price group 3 (size 6E, 7)
- Backrest upholstery price group 3 (size 6E, 7)
- Seat upholstery price group 4 (size 6E, 7)
- Backrest upholstery price group 4 (size 6E, 7)
- Felt floor protectors
- Chair frame chrome plated

## STANDARD

FEMB level:2017 (Level 3)

DIN EN 16139

## LOAD CAPACITY

125 kg

## SIZES

| | |
|---|---|
| CHAIR WIDTH | 46 cm |
| CHAIR HEIGHT | 112 cm |
| SEAT HEIGHT | 44 cm |
| DISTANCE SEAT TO FLOOR | 79 cm |
| CHAIR DEPTH | 50 cm |
| STACKABILITY | – |
| WEIGHT | 9 kg |

Our range of materials and colors can be found in the A2S material overview.

MADE IN GERMANY

A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM

# BAR STOOL
# MODEL 7899

## BENEFITS/SPECIALS

PAGHOLZ® from sustainable forestry

Optionally with grip hole, round or oval

Footrest natural lacquered

Optionally with seat and backrest upholstery (only sizes 6E, 7)

Indestructible PAGHOLZ® shell, scratch, break and impact resistant; flame retardant

Ergonomically and orthopedically adapted shell shape

Robust sled frame

## FABRIC PROPERTIES

**INTENSIVE Price group 1**
100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m2 +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100
**SKANDIA Price group 1**
100% polyester | flame retardant according to EN 1021 1 | 245 g/m2 +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100
**FLEECE Price group 1**
100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m2 | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100
**TAFF B1 Price group 2**
100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m2 +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100
**WOOL Price group 3**
100% wool | flame retardant according to EN 1021 1&2 | 460 g/m2 +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances
**PROTEX Price group 3**
surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m2 | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants
**ARTIFICIAL LEATHER Price group 3**
surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m2 +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances
**ARTIFICIAL LEATHER B1 Price group 4**
85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m2 | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants

A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM