FLEX GAS LIFT SWIVEL CHAIR MODEL 7873.200





STANDARD VERSION

Plastic shell ergonomically shaped. Material made of polypropylene, recyclable, manufactured in double-wall blown process. Thus soft sitting due to air cushioning effect, with integrated ventilation channels and groove to relieve the spine. Grip hole in the lumbar region and recessed grips on the upper edge of the backrest and underside of the chair.

Plastic 5-star base in black, with infinitely variable gas lift height adjustment. Round tubular column: 50 mm. With plastic feet.

OPTIONS

- Fully upholstered FLEX (size 5-7)
- 3D rocking mechanism

- Partial foot ring
- Felt floor protectors

- Load-dependent braking casters (SH +3 cm)
- Locking casters (SH +3 cm)

STANDARD

FEMB level:2017 (Level 3)

GS-zertifiziert gem. DIN EN 1729-1, DIN EN 1729-2

LOAD CAPACITY

125 kg

SIZES

| SIZE | 5-7 |
|--------------|----------|
| CHAIR WIDTH | 62 cm |
| CHAIR HEIGHT | 74-85 cm |
| SEAT HEIGHT | 38-49 cm |
| CHAIR DEPTH | 62 cm |
| STACKABILITY | - |
| WEIGHT | 9 kg |
| | |

Our range of materials and colors can be found in the A2S material overview.





FLEX GAS LIFT SWIVEL CHAIR MODEL 7873.200



BENEFITS/SPECIALS



Easy to carry due to low weight



Height adjustment by safety gas spring



Optional seat shell fully upholstered from size 5 onwards



Optionally with loaddependent braked casters



Optionally with partial foot ring



Seat shell with integrated ventilation channel



Extremely robust black plastic base

FABRIC PROPERTIES

FLEX upholstery

Flame retardant according to DIN 4102 B1 | 250 g/m2 +/-5% | 40,000 Martindale tours | Linting 4 | ÖKO-Tex 100