

PREMIUM OFFICE SWIVEL CHAIR WITH FULL UPHOLSTERY

MODEL 9348.101



STANDARD VERSION

Fully upholstered seat and back. Synchronous dynamic movement with locking of the back in 5 positions. Seat inclination and seat depth adjustable: back 20°, seat 6° as well as seat depth adjustment range 6 cm. Backrest 56 cm high, height adjustable by 8 cm, with lumbar support adjustment in the range 15 mm.

5-star aluminum base, with infinitely variable gas lift height adjustment including seat depth suspension: 45 - 56 cm. Polished aluminum base, with load-dependent braked safety casters.

OPTIONS

- Upholstery fabric price group 2
- Upholstery fabric price group 3
- Upholstery fabric price group 4
- Soft casters for hard floors

STANDARD

DIN EN 1729-1, DIN EN 1729-2

LOAD CAPACITY

110 kg

SIZES

CHAIR WIDTH	70 cm
CHAIR HEIGHT	100-116 cm
SEAT HEIGHT	45-56 cm
CHAIR DEPTH	70 cm
STACKABILITY	-
WEIGHT	14 kg

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM

PREMIUM OFFICE SWIVEL CHAIR WITH FULL UPHOLSTERY

MODEL 9348.101



BENEFITS/SPECIALS




Elegant, high-quality aluminum base



Load-dependent braked safety casters prevent unintentional rolling away



Ergonomically shaped backrest



Stepless gas lift height adjustment includes seat depth suspension



Self-weighting synchronous mechanism automatically adjusts spring force or resistance

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-TEX 100

SKANDIA Price group 1

100% polyester | flame retardant according to EN 1021 1 | 245 g/m² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-TEX 100

FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m² | 100,000 Martindale tours | linting 4 | ÖKO-TEX 100

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-TEX 100

WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 460 g/m² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m² | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m² +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780 +/-50 g/m² | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants