## FLEX Z-SHAPE CHAIR MODEL 7853





#### STANDARD VERSION

Plastic shell ergonomically shaped. Material made of polypropylene, recyclable, manufactured in double-wall blown process. Thus soft sitting due to air cushioning effect, with integrated ventilation channels and groove to relieve the spine. Grip hole in the lumbar region and recessed grips on the upper edge of the backrest and underside of the chair.

Z-shaped frame with 3D rocking effect, sizes 2-4 round tube: 22/2.5 mm, sizes 5-7 round tube: 22/3.0 mm, epoxy coated. With 3-component floor protector A2S FLOORSAFE®. To be placed on the table top.

#### **OPTIONS**

■ FLOORSAFE® felt floor protectors

Chair frame chrome plated

Fully upholstered FLEX (size 5-7)

#### STANDARD

FEMB level:2017 (Level 3)

DIN EN 1729-1, DIN EN 1729-2, DIN EN 16139

#### LOAD CAPACITY

125 kg

#### SIZES

SIZE	2	3	4	5	6	7
CHAIR WIDTH	39 cm	39 cm	39 cm	45 cm	45 cm	45 cm
CHAIR HEIGHT	62 cm	66 cm	69 cm	79 cm	82 cm	87 cm
SEAT HEIGHT	31 cm	35 cm	38 cm	43 cm	46 cm	51 cm
CHAIR DEPTH	37 cm	39 cm	39 cm	53 cm	53 cm	53 cm
STACKABILITY	2 pcs.					
WEIGHT	4 kg	4 kg	5 kg	6 kg	6 kg	6 kg

Our range of materials and colors can be found in the A2S material overview.







# FLEX Z-SHAPE CHAIR MODEL 7853



### BENEFITS/SPECIALS



Easy to carry due to low weight



3D movement through Z-frame supports the toning of the muscles



Optional seat shell fully upholstered from size 5 onwards



Seat shell with integrated ventilation channel



Robust Z-shape frame with A2S FLOORSAFE® floor protectors



Plate protectors protect the table when stacking up



2 chairs stackable and easy to carry due to low weight



Shell shape allows different sitting positions, including reverse

#### **FABRIC PROPERTIES**

 ${\sf FLEX}\ upholstery$ 

Flame retardant according to DIN 4102 B1 | 250 g/m2 +/-5% | 40,000 Martindale tours | Linting 4 | ÖKO-Tex 100