# CHANGE SLED BASE CHAIR MODEL 7802





## STANDARD VERSION

PAGHOLZ® waisted shell, with ergonomic three-dimensional shell shape and handle slot. Surface melamine coated and pore sealed with a scratch, impact and abrasion resistant finish created in the pressing process. Edges and waist are milled.

Sled base, round tube: 0.63"/0.08", seat shell with movable bearings, chrome-plated. With plastic floor protector.

### **OPTIONS**

- Seat upholstery price group 1
- Backrest upholstery price group 1
- Seat upholstery price group 2
- Backrest upholstery price group 2
- Seat upholstery price group 3
- Backrest upholstery price group 3
- Seat upholstery price group 4
- Backrest upholstery price group 4
- Felt floor protectors

#### STANDARD

FEMB level:2017 (Level 3)

DIN EN 1729-1, DIN EN 1729-2

### LOAD CAPACITY

276 lb

### SIZES

| SIZE         | 6       |
|--------------|---------|
| CHAIR WIDTH  | 20.08 " |
| CHAIR HEIGHT | 33.46 " |
| SEAT HEIGHT  | 18.11 " |
| CHAIR DEPTH  | 21.65 ' |
| STACKABILITY | 5 pcs.  |
| WEIGHT       | 18 lb   |

Our range of materials and colors can be found in the A2S material overview.









# CHANGE SLED BASE CHAIR MODEL 7802



# BENEFITS/SPECIALS



PAGHOLZ® from sustainable forestry



Optionally with seat and backrest upholstery



Indestructible PAGHOLZ® shell, scratch, break and impact resistant; flame retardant



Slender, stable sled frame



Shell design allows different seating positions, even reverse



Stackable up to 7 chairs (without upholstery)



Flexible seat shell ensures good blood circulation in the

### **FABRIC PROPERTIES**

### INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 8.82 oz/y² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100 SKANDIA Price group 1

100% polyester | flame retardant according to EN 10211 | 8.64 oz/y² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100 FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 14.18 oz/y² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 9.17 oz/y² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

WOOL Price group 3
100% wool | flame retardant according to EN 10211&2 | 16.23 oz/y² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 24.16 oz/y² | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

## ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 |  $15.34 \text{ oz/y}^2 + /-10\%$  | 100,000 Martindale tours | no linting | tested for harmful substances

#### ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit  $\int$  flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 27.51+/-1.76 oz/ $y^2$  | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants