

WAVE CANTILEVER CHAIR MODEL 7414



FEATURES

PAGHOLZ® shell, with ergonomic three-dimensional shell shape and high backrest, approx. 20.87", strongly waisted in the lower area. Surface melamine coated and pore sealed with a scratch, impact and abrasion resistant finish created in the pressing process. Seat and backrest with pressed-in texture.

Cantilever frame, firmly welded. Round tube: 0.87"/0.10". Frame chrome-plated, with plastic floor protectors.

OPTIONS

- Felt floor protectors
- Flat seat upholstery price group 1
- Flat seat upholstery price group 2
- Flat seat upholstery price group 3
- Flat seat upholstery price group 4
- Flat seat upholstery price group 1
- Flat seat upholstery price group 2
- Flat seat upholstery price group 3
- Flat seat upholstery price group 4
- WAVE seat upholstery
- WAVE leather seat upholstery
- WAVE backrest upholstery
- WAVE leather backrest upholstery

STANDARD

FEMB level:2017 (Level 3)

DIN EN 16139

LOAD CAPACITY

276 lb

SIZES

SIZE	SEAT HEIGHT	CHAIR HEIGHT	CHAIR WIDTH	CHAIR DEPTH	WEIGHT	STACKABILITY
6	18.11 "	36.22 "	17.32 "	20.47 "	22 lb	5 pcs.

Our range of materials and colors can be found in the A2S material overview.

WAVE CANTILEVER CHAIR MODEL 7414



BENEFITS/SPECIALS



PAGHOLZ® from sustainable forestry




Optionally with seat and back wave upholstery



Optionally with seat and back flat upholstery



Indestructible PAGHOLZ® shell, scratch, break and impact resistant, and flame retardant



Particularly high backrest increases seating comfort



Robust cantilever frame



Stackable up to 5 chairs (without upholstery)

FABRIC PROPERTIES

INTENSIVE price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 8.82 oz/y² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

SKANDIA price group 1

100% polyester | flame retardant according to EN 1021 1 | 8.64 oz/y² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

FLEECE price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 14.18 oz/y² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

TAFF B1 price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 9.17 oz/y² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

WOOL price group 3

100% wool | flame retardant according to EN 1021 1&2 | 16.23 oz/y² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

PROTEX price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 24.16 oz/y² | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 15.34 oz/y² +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 27.51 +/-1.76 oz/y² | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants

WAVE LEATHER

Genuine leather | flame retardant according to DIN 4102 B1

UPHOLSTERED WAVE

Flame retardant according to DIN 4102 B1 | 8.82 oz/yd² +/-5% | 40,000 Martindale rubs | Linting 4 | ÖKO-Tex 100

