

4-LEG CHAIR

MODEL 7470.010



STANDARD VERSION

Straight, rectangular seat shell, shaped to fit the body, with concealed screws. Made of multiplex, consisting of beech plywood, veneered crosswise. Standard in beech multiplex natural, environmentally friendly lacquered with water-based lacquer, edges softly rounded. 4-leg frame, with integrated stacking bar. Round tube: 0.79"/0.06". Frame chrome-plated, with plastic floor protector.

OPTIONS

- Shell with CPL coating
- Handle hole
- Seat upholstery price group 1 (size 6)
- Backrest upholstery price group 1 (size 6)
- Seat upholstery price group 2 (size 6)
- Backrest upholstery price group 2 (size 6)
- Seat upholstery price group 3 (size 6)
- Backrest upholstery price group 3 (size 6)
- Seat upholstery price group 4 (size 6)
- Backrest upholstery price group 4 (size 6)
- Felt joint floor protectors
- Teflon floor protector

STANDARD

DIN EN 1729-1, DIN EN 1729-2, DIN EN 16139

FEMB level:2017 (Level 3)

LOAD CAPACITY

276 lb

SIZES

SIZE	6
CHAIR WIDTH	20.87 "
CHAIR HEIGHT	35.43 "
SEAT HEIGHT	18.11 "
CHAIR DEPTH	21.65 "
STACKABILITY	9 pcs.
WEIGHT	15 lb

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM

4-LEG CHAIR MODEL 7470.010



BENEFITS/SPECIALS



Optionally with rectangular grip hole (not with backrest upholstery)



Optionally with seat and backrest upholstery



Seat shell optionally coated with scratch-resistant multiplex finish



Seat shell environmentally friendly lacquered with water-based varnish



Body contoured seat shell



Robust 4-leg frame



Stackable up to 9 chairs (with or without seat upholstery)

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 8.82 oz/y² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

SKANDIA Price group 1

100% polyester | flame retardant according to EN 1021 1 | 8.64 oz/y² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 14.18 oz/y² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 9.17 oz/y² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 16.23 oz/y² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 24.16 oz/y² | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 15.34 oz/y² +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 27.51 +/-1.76 oz/y² | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants