FLEX GAS LIFT SWIVEL CHAIR WITH FOOT RING MODEL 7873.202





STANDARD VERSION

Plastic shell ergonomically shaped. Material made of polypropylene, recyclable, manufactured in double-wall blown process. Thus soft sitting due to air cushioning effect, with integrated ventilation channels and groove to relieve the spine. Grip hole in the lumbar region and recessed grips on the upper edge of the backrest and underside of the chair.

Plastic 5-star base in black, with infinitely variable gas lift height adjustment. Round tubular column: 1.97". Version with elevation and heightadjustable foot ring, chrome-plated. With plastic feet.

OPTIONS

- Fully upholstered FLEX (size 5-7)
- Felt floor protectors

- Load-dependent braking casters (SH +1.18")
- Locking casters (SH +1.18")

STANDARD

FEMB level:2017 (Level 3)

GS-zertifiziert gem. DIN EN 1729-1, DIN EN 1729-2

LOAD CAPACITY

276 lb

SIZES

SIZE	5-7
CHAIR WIDTH	24.41"
CHAIR HEIGHT	33.46-41.34 "
SEAT HEIGHT	20.87-28.74 "
CHAIR DEPTH	24.41"
STACKABILITY	-
WEIGHT	23 lb

Our range of materials and colors can be found in the A2S material overview.







FLEX GAS LIFT SWIVEL CHAIR WITH FOOT RING MODEL 7873.202



BENEFITS/SPECIALS



Easy to carry due to low weight



Elevation with chrome-plated foot ring, height adjustable



Height adjustment by safety gas spring



Optional seat shell fully upholstered from size 5 onwards



Optionally with loaddependent braked casters



Seat shell with integrated ventilation channel

FABRIC PROPERTIES

FLEX upholstery

 $Flame\ retardant\ according\ to\ DIN\ 4102\ B1\ \Big|\ 8.82\ oz/yd^2\ +/-5\%\ \Big|\ 40,000\ Martindale\ tours\ \Big|\ Linting\ 4\ \Big|\ \ddot{O}KO-Tex\ 100\ Martindale\ tours\ \Big|\ Linting\ 4\ B^2$