

STANDARD OFFICE SWIVEL CHAIR WITH FULL UPHOLSTERY AND ARMRESTS

MODEL 9352.102



STANDARD VERSION

Fully upholstered seat and back. Synchronous mechanism with locking of the back in 4 positions. Seat inclination adjustable: back 22°, seat 13°. Backrest 22.05" high, height adjustable by 3.15", with lumbar support adjustment in the range 0.59".

5-star black plastic base with infinitely variable gas lift height adjustment, including seat depth suspension: 17.72" - 22.05". With load-dependent braked safety casters.

Including armrests in soft plastic, height adjustable by 3.15".

OPTIONS

- Upholstery fabric price group 2
- Upholstery fabric price group 3
- Upholstery fabric price group 4
- Soft casters for hard floors

STANDARD

DIN EN 1729-1, DIN EN 1729-2

LOAD CAPACITY

243 lb

SIZES

CHAIR WIDTH	27.56 "
CHAIR HEIGHT	39.37-45.67 "
SEAT HEIGHT	17.72-22.05 "
CHAIR DEPTH	27.56 "
STACKABILITY	-
WEIGHT	32 lb

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM

STANDARD OFFICE SWIVEL CHAIR WITH FULL UPHOLSTERY AND ARMRESTS

MODEL 9352.102



BENEFITS/SPECIALS



Elegant, sturdy black plastic base




Load-dependent braked safety casters prevent unintentional rolling away



Ergonomically shaped backrest



Height adjustable armrests



Stepless gas lift height adjustment includes seat depth suspension



Synchronous mechanism:
Spring force or resistance
adjustable to body weight

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 8.82 oz/y² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

SKANDIA Price group 1

100% polyester | flame retardant according to EN 1021 1 | 8.64 oz/y² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 14.18 oz/y² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 9.17 oz/y² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 16.23 oz/y² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 24.16 oz/y² | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 15.34 oz/y² +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4

85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 27.51 +/-1.76 oz/y² | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants