## FLEX GAS LIFT SWIVEL CHAIR MODEL 7876





#### STANDARD VERSION

Plastic shell ergonomically shaped. Material made of polypropylene, recyclable, manufactured in double-wall blown process. Thus soft sitting due to air cushioning effect, with integrated ventilation channels and groove to relieve the spine. Grip hole in the lumbar region and recessed grips on the upper edge of the backrest and underside of the chair.

Aluminum 5-star base, with infinitely variable gas lift height adjustment. Round tubular column: 1.97", epoxy coated. With plastic feet.

#### **OPTIONS**

- 3D rocking mechanism
- Polished aluminum base
- Felt floor protectors

- Partial foot ring
- Load-dependent braking casters (SH +1.18")

#### STANDARD

FEMB level:2017 (Level 3)

276 lb

LOAD CAPACITY

GS-zertifiziert gem. DIN EN 1729-1, DIN EN 1729-2

#### SIZES

| SIZE         | 3-5           |
|--------------|---------------|
| CHAIR WIDTH  | 21.26 "       |
| CHAIR HEIGHT | 25.59-29.92 " |
| SEAT HEIGHT  | 13.39-17.72 " |
| CHAIR DEPTH  | 21.26 "       |
| STACKABILITY | -             |
| WEIGHT       | 19 lb         |
|              |               |

Our range of materials and colors can be found in the A2S material overview.







# FLEX GAS LIFT SWIVEL CHAIR MODEL 7876



### BENEFITS/SPECIALS



Easy to carry due to low weight



Height adjustment by safety gas spring



Optionally with loaddependent braked casters



Optionally with partial foot ring



Seat shell with integrated ventilation channel



Extremely robust aluminum base