

# TEACHER LOCKER, WITH MAIL COMPARTMENTS (D 23.62")

MODEL 4284.250



## STANDARD VERSION

Body, 3-layer particle board (E1), melamine coated, highly abrasion-resistant, with 1 mm plastic edge, thickness 19 mm.

Rear panel, 3-layer chipboard (E1), melamine-coated, highly abrasion-resistant, grooved all around, thickness 8 mm.

Back panel, 3-layer chipboard (E1), melamine coated, highly abrasion-resistant, grooved all around, thickness 8 mm.

Cabinet including base.

Teacher compartments individually lockable.

**Note:** 1 folder height (OH)  $\hat{=}$  38.4 cm

## OPTIONS

- Decoration group 2
- Front decors price group 2
- Front HPL glued
- Shelf (additional)
- Handle PG 2
- Lock with pin cylinder change core
- Base adjustment
- Steel base (chrome silver 9006)
- Doors different colors

## STANDARD

DIN EN 14074, DIN EN 14073-2, DIN EN 14073-3, DIN EN 16121, DIN EN 16122

FEMB level:2017 (Level 3)

## TECHNICAL SPECIFICATIONS

|                   |                    |
|-------------------|--------------------|
| FOLDER HEIGHT     | 5                  |
| WIDTH             | 16.14 "            |
| TOTAL HEIGHT      | 80.31 "            |
| DEPTH             | 23.62 "            |
| INSIDE MEASURE    | 3.15x14.57x21.26 " |
| COMPARTMENTS      |                    |
| NO. OF            | 3                  |
| COMPARTMENTS      |                    |
| NO. OF ADJUSTABLE | 1                  |
| SHELVES           |                    |
| WEIGHT            | 172 lb             |

Our range of materials and colors can be found in the A2S material overview.



A2S-Furnishing Systems Ltd.  
ASS-Einrichtungssysteme GmbH  
info@a2s.com  
WWW.A2S.COM

# TEACHER LOCKER, WITH MAIL COMPARTMENTS (D 23.62")

MODEL 4284.250



## BENEFITS/SPECIALS




Board material melamine coated with robust plastic edge



Metal cup hinges with 240° opening angle




Optionally with robust steel base



Cupboard with central locking



Carcass firmly dowelled and glued ex works



Resistance to warping due to 8 mm thick back wall