MULTI-PURPOSE TABLE, TWO-SEATER (62.99"X31.50")

MODEL 1960.168





STANDARD VERSION

Tabletop, 3-layer chipboard (E1), melamine coated, highly abrasion-resistant, with 0.12" plastic edge, thickness: 0.98". **Note:** Table height specifications refer to a tabletop thickness of 0.98".

C-shape double column base frame, side parts oval tube: 1.97"/1.18"/0.08". Crossbars rectangular tube: 1.57"/0.79"/0.08". Extension arm top rectangular tube: 1.97"/1.18"/0.08". Cross frame square tube: 1.18"/1.18"/0.08". Frame prepared to accept various attachments. Frame epoxy coated, with floor protectors with step protection.

OPTIONS

- Table top HPL glued
- Felt floor protectors
- Floor leveler
- Floor mounting
- Cable opening, Ø 3.15"

- Cable opening, Ø 3.54"
- CPU holder
- CPU cabinet open
- CPU cabinet closed
- Mesh cable duct

- Cable slack
- 6-fold gounded socket
- Connecting fitting for table-to-table combination
- Cable riser duct

STANDARD

DIN EN 1729-1, DIN EN 1729-2

FEMB level:2017 (Level 3)

SIZES

SIZE	72 cm
TABLE WIDTH	62.99
TABLE HEIGHT	28.35
TABLE DEPTH	31.50
STACKABILITY	
NUMBER OF SEATS	2
WEIGHT	86 lb

Our range of materials and colors can be found in the A2S material overview.







MULTI-PURPOSE TABLE, TWO-SEATER (62.99"X31.50") MODEL 1960.168



BENEFITS/SPECIALS



Melamine coated table top with robust plastic edge



Floor protectors with integrated step protection



Due to C-shape no disturbance of the table legs when getting in and out of the table