WOODMARK C-FRAME CHAIR WITH SEAT AND BACKREST UPHOLSTERY

MODEL 7106

STANDARD VERSION

Seat and back separate and shaped to fit the body. Seat support made of beech plywood, fully upholstered all round.
C-shape frame, side part oval tube: 1.38"/0.59"/0.08", seat support rectangular tube: 1.18"/0.59"/0.08", cross strut oval tube: 1.38"/150.59"/0.06", standard version epoxy coated. Including plate protector to sit on the table top. Floor protector with step protection.

OPTIONS

- Upholstery fabric price group 2
- Upholstery fabric price group 3
- Upholstery fabric price group 4
- Seat and back riveted
- Felt floor protectors
- Row connection

STANDARD

FEMB level:2017 (Level 3)

DIN EN 1729-1, DIN EN 1729-2

LOAD CAPACITY

276 lb

SIZES

SIZE	6	7
CHAIR WIDTH	17.72 "	17.72 "
CHAIR HEIGHT	31.10 "	32.68 "
SEAT HEIGHT	18.90 "	20.47 "
CHAIR DEPTH	20.08 "	20.08 "
STACKABILITY	–	–
WEIGHT	15 lb	17 lb

Our range of materials and colors can be found in the A2S material overview.

MADE IN GERMANY

A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM

WOODMARK C-FRAME CHAIR WITH SEAT AND BACKREST UPHOLSTERY

MODEL 7106

BENEFITS/SPECIALS

Floor protectors with integrated step protection

Plate protectors protect the table when stacking

With seat and backrest upholstery



Optionally with row connection

Stable and solid C-shape frame

No disturbance of the chair legs when getting in and out of the chair

FABRIC PROPERTIES

INTENSIVE Price group 1
100% polyester | flame retardant according to EN 1021 1&2 | 8.82 oz/y² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100
SKANDIA Price group 1
100% polyester | flame retardant according to EN 1021 1 | 8.64 oz/y² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100
FLEECE Price group 1
100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 14.18 oz/y² | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100
TAFF B1 Price group 2
100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 9.17 oz/y² +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100
WOOL Price group 3
100% wool | flame retardant according to EN 1021 1&2 | 16.23 oz/y² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances
PROTEX Price group 3
surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 24.16 oz/y² | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants
ARTIFICIAL LEATHER Price group 3
surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 15.34 oz/y² +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances
ARTIFICIAL LEATHER B1 Price group 4
85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 27.51+/-1.76 oz/y² | 75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants

A2S-Furnishing Systems Ltd.
ASS-Einrichtungssysteme GmbH
info@a2s.com
WWW.A2S.COM