

STANDARD VERSION

Top, 3-layer chipboard (E1), melamine coated, highly abrasion resistant, with 3 mm plastic edge, thickness: 25 mm.

OPTIONS

- Decoration group 2
- magnetic
- Upholstery fabric Intensive
- Cover fabric Skandia Cover fabric fleece
- Upholstery fabric TAFF B1 (price
- group 2)
- Upholstery fabric WOOL (price group
- Frame chrome plated

TECHNICAL SPECIFICATIONS

WIDTH 68.82 " 18.11 " HEIGHT WEIGHT 57 lb

BENEFITS/SPECIALS



Mounting by means of Allen screw on the table top



Optionally with fabric cover



Ideal as a view and sound insulation

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 8.82 oz/y² +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

SKANDIA Price group 1

100% polyester | flame retardant according to EN 1021 1 | 8.64 oz/y² +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 14.18 oz/y² | 100,000 Martindale tours | linting 4 | ÖKO-Tex

TAFF B1 Price group 2

 $100\% \ polyester \ | \ flame \ retardant \ according \ to \ EN \ 1021 \ 1\&2, \ DIN \ 4102 \ B1 \ | \ 9.17 \ oz/y^2 \ +/-5\% \ | \ 70,000 \ Martindale \ tours \ | \ linting \ polyester \ | \$ 5 | ÖKO-Tex 100

WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 16.23 oz/y² +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances