



## STANDARD VERSION

Unterkonstruktion aus stabiler 3-Schicht-Spanplatte mit Polsterung aus Schaumstoff. Rundfüße pulverbeschichtet in RAL 7021 schwarzgrau aus Stahl. Farben der Lehne und Sitzfläche getrennt innerhalb einer Stoffgruppe wählbar.

Alle Elemente der Serie sind miteinander verkettbar.

Sitzhöhe: 38 cm

## OPTIONS

- Upholstery fabric TAFF B1 (price group 2)
- Upholstery fabric PROTEX (price group 3)
- Upholstery fabric WOOL (price group 3)
- Bezugsstoff PROTEX B1

## TECHNICAL SPECIFICATIONS

<b>TOTAL WIDTH</b>	47.24 "
<b>TOTAL HEIGHT</b>	14.96 "
<b>SEAT HEIGHT</b>	14.96 "
<b>TOTAL DEPTH</b>	23.62 "
<b>SEAT DEPTH</b>	23.62 "
<b>WEIGHT</b>	51 lb

## FABRIC PROPERTIES

### FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 14.18 oz/y<sup>2</sup> | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

### TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 9.17 oz/y<sup>2</sup> +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

### WOOL Price group 3

100% wool | flame retardant according to EN 1021 1&2 | 16.23 oz/y<sup>2</sup> +/-5% | 35,000 Martindale tours | linting 4 | tested for harmful substances

### PROTEX Price group 3

surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 24.16 oz/y<sup>2</sup> | 300,000 Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant, resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

### PROTEX B1 price group 4

surface 100% vinyl / fabric 100% cotton | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 760 g/m<sup>2</sup> | 300.000 tours Martindale | no linting

**SPECIAL PROPERTIES:** PERMABLOK3® - protection against germs, abrasion and stains: Antibacterial, antifungal, stain resistant, sulfide stain resistant, anti-fungal protection - mildew resistant backing and surface | disinfectant resistant, easy cleaning - wipeable with soap and water | antistatic surface

**Tested to:** ISO206B02 7/8 UV resistance | ISO 18184 & ISO 21702 virus-free surface to reduce corona virus | ISO 22196 for bacteria-free surface | ISO 16000 indoor air emission class A+

**Tested for:** Plasticizers and harmful substances - material requirements of toy standards EN 71-3 Safety of toys (migration of certain elements) and 2005/84/EC (phthalates in toys and childcare articles)